

Datasheet

Generated on: 2026-09-10 23:41

BuyLabels

support@buylabels.eu

Product

Product name	Thermal labels, 76 x 51mm, 1370 labels, freezer-safe
Article number	Z-76-51-25-FR
Sold per	1 piece
Unit	piece / pieces
Weight	802 g per piece



Compatible printers

Bixolon	SLP-DX220, SLP-DX223, SLP-DX420, SLP-DX423, SLP-TX220, SLP-TX223, SLP-TX420, SLP-TX423, XD3-40, XD3-43, XD5-40, XD5-43, XD5-T40, XD5-T43, XM7-20, XM7-30, XM7-40, XT2-40, XT5-40, XT5-43, XT5-46
Citizen	CL-E300, CL-E321, CL-E720, CL-S300, CL-S321, CL-S400DT, CL-S521, CL-S621, CL-S631, CL-S700, CL-S700DT, CL-S703, CL-S6621
Godex	EZ-1100PLUS, EZ-1300PLUS, EZ-2050, EZ-2150, EZ-2200, EZ-2250i, EZ-2300, EZ-2350i, EZ-6200PLUS-E, EZ-6300PLUS-E, EZ-PI1200, EZ-PI1300, G-300, G-330, G-500, G-530, RT-200, RT-200i, RT-230, RT-230i, RT-700, RT-700i, RT-730, RT-730i, RT-860i, ZX-1X00i, ZX-420, ZX-430, ZX-1200i, ZX-1300i, ZX-1600i
Honeywell	E-CLASS MK III, I-CLASS MK II, M-CLASS MK II, PC42T, PC43T, PD43, PD45, PD45S, PM42, PM43, PM45, PX4I, PX6I, PX940, PX940V
Sato	CL4NX, CL4NX Plus, CL6NX, CL6NX Plus, CT4-LX, CT4-LX DT, CT4i, CT408i DT, LM408e, LM412e, TG3, TG308, TG312, TG408, WS2, WS4, WS4 DT
TSC	DA210, DA220, DA310, DA320, ME240, ME340, ML240P, ML340P, TA210, TA310, TC200, TC210, TC300, TC310, TDP-247, TE200, TE210, TE300, TE310, TTP-243, TTP-244, TTP-245C, TTP-246M, TTP-247, TTP-334M, TTP-343C, TTP-346MT, TTP-644MT, TTP-2410MT, TX200, TX300, TX600
Toshiba	B-EP2DL, B-EP4DL, B-EV4D, B-EV4T, B-EX4D2, B-EX4T1, B-EX4T2, B-FV4D, B-FV4T, B-SA4TM, B-SA4TP

Dimensions

Width	76 mm
Height	51 mm
Labels per roll	1370
Core diameter	25 mm
Outer diameter	115 mm
Corner radius	2 mm
Shape	Rectangular

Roll / detection

Perforation	Yes
Winding	Outside wound
Sensor / detection	Gap detection
Spacing between labels	3 mm
Detection gap	No
Black mark	No

Material and adhesive

Material	Polypropylene
Printing method	Direct thermal
Colour	White
Glue	Permanent freezer-safe
Adhesive weight	15 g/m ²
Thermal coating	TOP / topcoated
Ribbon required	No

Use and compliance

Use temperature	-20 °C to 60 °C
Minimum labeling temperature	-15 °C
Storage conditions	For optimal processing and preservation of material properties, store in the original closed packaging at 23°C (±2°C) and 50% relative humidity. Avoid direct exposure to UV light, high temperatures, moisture and heat sources.
BPA-free	Yes
BPS-free	Yes
BPF-free	Yes
Phthalate-free	Yes

Regulatory & trade information

EU responsible economic operator	BuyLabels Pieter Schotsmanstraat 42 1931 AR Egmond aan Zee Netherlands
Country of origin	CN
HS code	3919108090
Customs description	Self-adhesive plastic labels

Product page

<https://www.buylabels.eu/thermal-labels-76-x-51mm-1370-labels-freezer-safe>

Scan the QR code to open the product page or place an order.



Contact

BuyLabels
Pieter Schotsmanstraat 42
1931 AR Egmond aan Zee

Netherlands
support@buylabels.eu

This datasheet is generated automatically from the available product data. No rights can be derived from this document.